

IN THE CLAIMS

Please amend the claims as follows:

1. (original) A device for operating a high-pressure discharge lamp, comprising:

a switched-mode power supply circuit for supplying power to the high-pressure discharge lamp from a supply voltage, the power supply circuit comprising at least one power switching element;

control means for controlling the at least one power switching element in its switched-on and switched-off states for controlling the power or current supplied to the high-pressure discharge lamp;

wherein the control means are adapted to control the power consumed by the lamp during its steady phase or the current consumed by the lamp during its run-up phase by controlling the on-time (T_{on}) of the switched-on state of the at least one power switching element.

2. (original) A device according to claim 1, wherein the value of the on-time (T_{on}) of the at least one power switching element is a preset value, the preset value depending on the specifications of the type of discharge lamp used.

3. (currently amended) A device according to claim 1~~or 2~~, wherein the on-time (T_{on}) of the at least one power switching element for a specific discharge lamp type is substantially constant.

4. (currently amended) A device according to ~~any one of the preceding claims~~claim 1, comprising:

- input current determining means for determining the input current of the power supply, the input current determining means providing a signal representative of the determined input current;

- a feedback means through which said signal is fed back to the control means, wherein the control means are adapted to control the on-time (T_{on}) of the at least one switching element as a function of said feedback signal.

5. (currently amended) A device according to ~~any one of the preceding claims~~claim 1, comprising

- voltage determining means for determining the lamp voltage, the voltage determining means providing a signal representative of the determined lamp voltage,

- a feedback means through which said signal is fed back to the control means;

wherein the control means are adapted to control the on-time (T_{on}) of the at least one power switching element as a function of said feedback signal.

6. (currently amended) A device according to ~~any one of the preceding claims~~ claim 1, comprising a dim level means for setting a reduced lamp power level, the dim level means providing a signal representative of the dim level of the lamp, wherein the control means are adapted to control the on-time (T_{on}) of the at least one power switching element as a function of said signal.

7. (currently amended) A device according to claim 5 ~~or 6~~, wherein the control means comprise a feedback controller for controlling the control means.

8. (original) A device according to claim 7, wherein the control means are adapted to provide fast lamp power adjustments and the feedback controller is adapted to provide relatively slow lamp power adjustments.

9. (currently amended) A device according to ~~any one of claims 4-8~~ claim 4, wherein the on-time (T_{on}) is iteratively adapted with a

iteration frequency lower than the switching frequency of the switched-mode power supply.

10. (currently amended) A device according to ~~any one of the preceding claims~~claim 1, wherein the switching frequency of the switched-mode power supply is at least 100 kHz.

11. (original) A device according to claim 9, wherein the iteration frequency is 100 Hz or less, preferably about 10 Hz or less.

12. (currently amended) A device according to ~~any one of the preceding claims~~claim 1, wherein use is made of a half or full-bridge power supply and a filter circuit comprising a series inductor (L) and at least one filter capacitor (C) parallel to the lamp.

13. (currently amended) A device according to ~~any of the preceding claims~~claim 1, wherein the switched-mode power supply comprises a half-bridge or full-bridge commutating forward topology.

14. (currently amended) A device according to ~~any one of the~~
~~claims 1-13~~claim 1, wherein the switched-mode power supply
comprises a down-converter

15. (original) A method of operating a high-pressure discharge
lamp, comprising:

supplying power to the high-pressure discharge lamp from
a supply voltage, using at least one power switching element;

controlling the power consumed by the lamp during its
steady phase using control means;

wherein said control means control the lamp power during the steady
state of the lamp by fixing the on-time (T_{on}) of the at least one
power switching element.

16. (original) A method according to claim 15, comprising
presetting the value of the on-time (T_{on}) of the at least one power
switching element depending on the specifications of the type of
discharge lamp used.

17. (currently amended) A method according to ~~any one of the~~
~~claims 15-16~~claim 15, wherein the on-time (T_{on}) of the at least one
power switching element is kept substantially constant.

18. (currently amended) A method according to ~~any one of the~~
~~claims 15-17~~claim 15, comprising determining the lamp voltage,
providing a signal representative of the determined lamp voltage,
feeding said signal back to the control means and adapting the on-
time (T_{on}) of the at least one power switching element as a function
of the determined lamp voltage.